



产品特性/Product Features

- IP6K9K
- 10A 85°C
- 12-750VDC
- 1000MΩ (1000VDC) , IEC 60664-1
-

		1a	
		4.5mΩ (at 10A)	
		10A	
		2×10 ⁻⁵	
		450V型	750V型
		1000VDC	1000VDC
		100A(320VDC)1	100A(320VDC)1
		4.5kW	7.5kW
1)		1×10 ⁻⁵ 450VDC,10A)	1×10 ⁻⁵ 750VDC,10A)
		10A:	
		15A:1h	
		20A:20min	
		40A:30s	
		60A:10s	
		100A:0.6s	
1)	23°C,	0.6s:5.4s.	
2)	85°C,	2.5 mm ² , " "	

		1000MΩ(1000VDC)
		3000VAC 1min
		3000VAC 1min
()		≤30ms
()		≤10ms
		196m/s ²
		490m/s ²
		10Hz ~ 500Hz 49m/s ²
		5% ~ 85%RH
		-40°C ~ 85°C
		QC
		150g
		66.8mm×39.0mm×48.2mm

VDC	VDC	VDC	W
12	9	1	2.6
24	≤18	≥2	2.6

-40°C ~ 85°C)



10mm ±0.2mm

10-50 mm ±2mm

2

