



**产品特性/Product Features**

- IP6K9K
- 100A 85°C
- 12-750VDC
- 1000MΩ (1000VDC) , IEC 60664-1

High Voltage Ceramic Contactors	
	1a
	≤3mΩ (at 20A)
	100A
	2×10 <sup>5</sup>
	<b>450V型</b>
	1000VDC
	1000A(320VDC)1
	45kW
1)	2×10 <sup>-4</sup> 22.5VDC, =1ms 400A, 100A
	1 360VDC, =1ms 1350A, 100A
	1×10 <sup>-4</sup> 360VDC,50A
	: 3×10 <sup>-3</sup> 450VDC,100A
	<b>750V型</b>
	1000VDC
	1000A(320VDC)1
	75kW
	2×10 <sup>-4</sup> 37.5VDC, =1ms 400A, 100A
	6×10 <sup>-3</sup> 600VDC,50A
	: 1×10 <sup>-3</sup> 750VDC,100A
2)	100A:
	120A:2h
	200A:10min
	400A:2min
	600A:30s
	1000A:0.6s
1)	23°C, 0.6s:5.4s.
2)	85°C, 40 mm <sup>2</sup> , " "

1000MΩ(1000VDC)	
	3000VAC 1min
	3000VAC 1min
( )	≤30ms
( )	≤10ms
	196m/s <sup>2</sup>
	490m/s <sup>2</sup>
	10Hz ~ 500Hz 49m/s <sup>2</sup>
	5% ~ 85%RH
	-40°C ~ 85°C
	M5
	350g
	76.5mm×39.0mm×77.0mm

VDC	VDC	VDC	W
12	9	1	4.5
24	≤18	≥2	4.5

-40°C ~ 85°C)

1. 2. 3. 4. 5. 6. 7. 8. 9. 10. 11. 12. 13. 14. 15. 16. 17. 18. 19. 20. 21. 22. 23. 24. 25. 26. 27. 28. 29. 30. 31. 32. 33. 34. 35. 36. 37. 38. 39. 40. 41. 42. 43. 44. 45. 46. 47. 48. 49. 50. 51. 52. 53. 54. 55. 56. 57. 58. 59. 60. 61. 62. 63. 64. 65. 66. 67. 68. 69. 70. 71. 72. 73. 74. 75. 76. 77. 78. 79. 80. 81. 82. 83. 84. 85. 86. 87. 88. 89. 90. 91. 92. 93. 94. 95. 96. 97. 98. 99. 100.

/Unit mm



